

62/05/02



02-08-02

JC10 Rec'd PCT/PTO 05 FEB 2002

Form PTO 1390
(Rev. 1-98)U.S. Department of Commerce Patent
and Trademark OfficeATTORNEY DOCKET NO.
E227.312-0015TRANSMITTAL LETTER TO THE UNITED STATES
DESIGNATED/ELECTED OFFICE (DO/EO/US)
CONCERNING A FILING UNDER 35 U.S.C. 371U.S. APPLICATION NO. (If known, see 37
C.F.R. 1.57)
10/049352

INTERNATIONAL APPLICATION NO.

INT'L FILING DATE

PRIORITY DATE
CLAIMED
August 10, 1999

PCT/GB00/03004

August 3, 2000

TITLE OF INVENTION: **LINEAR ACCELERATOR**APPLICANT(S) FOR DO/EO/US: **John ALLEN et al.**

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. This is a FIRST submission of items concerning a filing under 35 U.S.C. 371.
2. This is a SECOND or SUBSEQUENT submission of items concerning a filing under 35 U.S.C. 371.
3. This express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1).
4. A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.
5. A copy of the International Application as filed (35 U.S.C. 371(c)(2))
 - a. is transmitted herewith (required only if not transmitted by the International Bureau).
 - b. has been transmitted by the International Bureau.
 - c. is not required, as the application was filed in the United States Receiving Office (RO/US).
6. A translation of the International Application into English (35 U.S.C. 371(c)(2)).
7. Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3))
 - a. are transmitted herewith (required only if not transmitted by the International Bureau).
 - b. have been transmitted by the International Bureau.
 - c. have not been made; however, the time limit for making such amendments has NOT expired.
 - d. have not been made and will not be made.
8. A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
9. An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).
10. A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).

Items 11 to 16 below concern other document(s) or information included:

11. An Information Disclosure Statement under 37 C.F.R. 1.97 and 1.98.
12. An assignment document for recording. A separate cover sheet in compliance with 37 C.F.R. 3.28 and 3.31 is included.
13. A FIRST preliminary amendment.
- A SECOND or SUBSEQUENT preliminary amendment.
14. A substitute specification.
15. A change of power of attorney and/or address letter.
16. Other items or information:
 - a. WO 01/11928
 - b. File Data Sheet
 - c. Notification Concerning Submission or Transmittal of Priority Document
 - d. Notification of Transmittal of the International Preliminary Examination Report

U.S. APPLICATION NO (If known, see 37 C.F.R. 1.57) 10/049352	INTERNATIONAL APPLICATION NO. PCT/GB00/03004	ATTORNEY'S DOCKET NUMBER E227.312-0015		
17. [X] The following fees are submitted: BASIC NATIONAL FEE (37 C.F.R. 1.492(a)(1)-(5)):		CALCULATIONS PTO USE ONLY		
International preliminary examination and search fees not paid to USPTO and International Search Report not prepared by the EPO or JPO \$ 1040.00 International Search Report prepared by the EPO or JPO \$ 890.00 International search fee paid to the USPTO \$ 740.00 International preliminary examination fee paid to USPTO \$ 710.00 International preliminary examination fee paid to USPTO and all claims satisfied provisions of PCT Article 33(1)-(4) \$ 100.00				
ENTER APPROPRIATE BASIC FEE AMOUNT		= \$890.00		
Surcharge of \$130 for furnishing the oath or declaration later than <u>20</u> <u>30</u> months from the earliest claimed priority date (37 C.F.R. 1.492(e)).		\$ 0		
Claims	Number Filed	Number Extra	Rate	
Total claims	9 - 20 =		X \$ 18.00	\$ 0
Ind. Claims	2 - 3 =		X \$ 84.00	\$ 0
Multiple dependent claim(s) (if applicable)			+ \$280.00	\$ 0
TOTAL OF ABOVE CALCULATIONS		=	\$ 890.00	
Reduction by $\frac{1}{2}$ for filing by small entity, if applicable. (Note 37 C.F.R. 1.27).			\$ 0	
		SUBTOTAL =	\$ 890.00	
Processing fee of \$130.00 for furnishing the English translation later the <u>20</u> <u>30</u> months from the earliest claimed priority date (37 C.F.R. 1.492(f)).		+ \$ 0		
		TOTAL NATIONAL FEE =	\$ 890.00	
Fee for recording the enclosed assignment (37 C.F.R. 1.21(h)). The Assignment must be accompanied by an appropriate cover sheet. (37 C.F.R. 3.28, 3.31). \$40.00 per property		+ \$ 40.00		
		TOTAL FEES ENCLOSED =	\$ 930.00	
		Amount to be refunded:	\$	
		Charged:	\$	
a. <input checked="" type="checkbox"/> A check in the amount of \$930.00 to cover the above fees is enclosed. b. <input type="checkbox"/> Please charge my Deposit Account No. 11-0982 in the amount of <u> </u> to cover the above fees. A duplicate copy of this sheet is enclosed. c. <input checked="" type="checkbox"/> The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. 11-0982. A duplicate copy of this sheet is enclosed.				
NOTE: Where an appropriate time limit under 37 C.F.R. 1.494 or 1.495 has not been met, a petition to revive (37 C.F.R. 1.137(a) or (b)) must be filed and granted to restore the application to pending status.				

KINNEY & LANGE, P.A.
THE KINNEY & LANGE BUILDING
312 South Third Street
Minneapolis, Minnesota 55415-1002
Telephone: 612/339-1863 Telefacsimile: 612/339-6580

Jeffrey D. Shewchuk

Use Express Mail only on initial filing of national stage in the U.S. (371) or filing Missing Parts

Express Mail No.: EL705881249US

Date of Deposit: February 5, 2002

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

First Named	
Inventor	: John ALLEN et al.
Appln. No.	:
Filed	: February 5, 2002
Title	: LINEAR ACCELERATOR
Docket No.	: E227.312-0015

Group Art Unit:
Examiner:

PRELIMINARY AMENDMENT

Box Non-Fee Amendment
Assistant Commissioner for Patents
Washington, D.C. 20231

SENT VIA EXPRESS MAIL

Express Mail No.: EL705881249US

Sir:

Prior to calculation of the filing fee and examination please amend the above-identified application as follows:

IN THE ABSTRACT

Please add the following abstract on a separate sheet:

IN THE ABSTRACT

An accelerator comprises a plurality of accelerating cells arranged to convey a beam, adjacent cells being linked by a coupling cell, the coupling cells being arranged to dictate the ratio of electric field in the respective adjacent accelerating cells, at least one coupling cell being switchable between a positive ratio and a negative ratio. Such an accelerator in effect inserts a phase change into the E field by imposing a negative ratio, meaning that the beam will meet a reversed electric field in subsequent cells and will in fact be decelerated. As a result, the beam can be developed and bunched in early cells while accelerating to and/or at relativistic energies, and then bled of energy in later cells to bring the beam energy down to (say) between 100 and 300 KeV. Energies of this magnitude are comparable to diagnostic X-rays, where much higher contrast of bony structures exists. Hence the accelerator can be used to take kilovoltage portal images.

卷之三

IN THE CLAIMS

Please cancel claim 10 without prejudice. Please amend claims 3, 4 and 9 (marked up version attached in Appendix), such that pending claims 1-9 are as follows:

1. An accelerator comprising a plurality of accelerating cells arranged to convey a beam, adjacent cells being linked by a coupling cell, the coupling cells being arranged to dictate the ratio of electric field in the respective adjacent accelerating cells, at least one coupling cell being variable to allow a range of ratios including positive values and negative values.
2. An accelerator according to claim 1 in which the at least one coupling cell is variable smoothly from a positive value to a negative value.
3. (Amended) An accelerator according to claim 1, in which the beam is relativistic over substantially the length of the accelerator.
4. (Amended) An accelerator according to claim 1, in which the variable coupling cell comprises a cavity containing a conductive element rotatable about an axis transverse to the beam axis.
5. The use of an accelerator in which a plurality of accelerating cells are arranged to convey a beam, and adjacent cells are linked by a coupling cell, the coupling cells being arranged to dictate the ratio of electric field in the respective adjacent accelerating cells, at least one coupling cell being variable to allow a range of ratios including positive values and negative values.
6. Use according to claim 5 in which the at least one coupling cell is variable smoothly from a positive value to a negative value.
7. An operating method for an accelerator in which a plurality of accelerating cells are arranged to convey a beam, and adjacent cells are linked by a coupling cell, the coupling cells being

arranged to dictate the ratio of electric field in the respective adjacent accelerating cells, at least one coupling cell being variable to allow a range of ratios including positive values and negative values.

8. The method of claim 7 in which the at least one coupling cell is variable smoothly from a positive value to a negative value.
- 9.(Amended) The use of an accelerator according to claim 1, for taking kilovoltage portal images.


REMARKS

It is respectfully requested that the above amendments be made prior to calculating the filing fee. In this Preliminary Amendment, the claims are amended to remove multiple dependencies, and the Abstract is provided on a separate sheet. The Examiner is invited to contact the undersigned attorney at the number listed below if such a call would in any way facilitate examination of the application.

Respectfully submitted,

KINNEY & LANGE, P.A.

By _____


Jeffrey D. Shewchuk, Reg. No. 37,235
THE KINNEY & LANGE BUILDING
312 South Third Street
Minneapolis, MN 55415-1002
Telephone: (612) 339-1863
Fax: (612) 339-6580

Date: February 5, 2002

JDS:beh

APPENDIX:
MARKED UP VERSION OF SPECIFICATION AND CLAIM AMENDMENTS

IN THE CLAIMS

Please cancel claim 10 without prejudice. Please amend claims 3, 4 and 9 as follows:

3. (Amended) An accelerator according to claim 1 [or claim 2] in which the beam is relativistic over substantially the length of the accelerator.

4. (Amended) An accelerator according to [any one of the preceding claims] claim 1, in which the variable coupling cell comprises a cavity containing a conductive element rotatable about an axis transverse to the beam axis.

9.(Amended) The use of an accelerator according to [any one of claims 1 to 4] claim 1, for taking kilovoltage portal images.

4/P>

LINEAR ACCELERATOR

FIELD OF THE INVENTION

The present invention relates to a linear accelerator.

BACKGROUND ART

In the use of radiotherapy to treat cancer and other ailments, a powerful beam of the appropriate radiation is directed at the area of the patient which is affected. This beam is apt to kill living cells in its path, hence its use against cancerous cells, and therefore it is highly desirable to ensure that the beam is correctly aimed. Failure to do so may result in the unnecessary destruction of healthy cells of the patient. Several methods are used to check this, and an important check is the use of a so-called "portal image". This is an image produced by placing a photographic plate or electronic imaging plate beneath the patient during a brief period of irradiation. The

beam is attenuated by the patient's internal organs and structures, leaving an image in the plate. This can then be checked either before complete treatment or after a dose, to ensure that the aim was correct.

Portal images are however extremely difficult to interpret. The energy of the beam which is necessary to have a useful therapeutic effect is very much greater than that used for medical imaging. At these higher energies there is smaller ratio in the relative attenuation between bony and tissue structure, which results in portal images with poor contrast. Structures within the patient are difficult to discern.

Some existing radiotherapy devices include a second radiation source which is adapted to produce a lower energy beam for producing a portal image. This second source is usually placed either alongside the principal accelerator and parallel thereto, or is mounted at an angle such that the entire unit is rotated about the patient to bring the second source into line for the portal image, following which the unit is rotated back for treatment. Both arrangements present difficulties in ensuring adequate alignment between the principal accelerator and the second source.

It has not hitherto been possible simply to reduce the energy of the principal (therapeutic) accelerator, since this must operate in a relativistic mode in order to maintain beam quality. If the final beam energy is too low, then the beam will be non-relativistic at earlier parts of the accelerator, preventing satisfactory operation.

SUMMARY OF THE INVENTION

The present invention therefore provides an accelerator comprising a plurality of accelerating cells arranged to convey a beam, adjacent cells being linked by a coupling cell, the coupling cells being arranged to dictate the ratio of electric field in the respective adjacent accelerating cells, at least one coupling cell being switchable between a positive ratio and a negative ratio.

Such an accelerator is eminently suitable for therapeutic use as part of a radiotherapy apparatus as a phase change is in effect inserted into the E field by imposing a negative ratio meaning that the beam will meet a reversed electric field in subsequent cells and will in fact be decelerated. As a result, the beam can be developed and bunched in early cells while accelerating to and/or at relativistic energies, and then bled of energy in later cells to bring the beam energy down to (say) between 100 and 300 KeV. Despite this low output energy, the beam is relativistic over substantially the same length of the accelerator, as previously. Energies of this magnitude are comparable to diagnostic X-rays, where much higher contrast of bony structures exists. Hence the accelerator can be used to take kilovoltage portal images.

It is preferred that the switchable coupling cell comprises a cavity containing a conductive element rotatable about an axis transverse to the beam axis. This is more preferably as set out in our earlier application PCT/GB99/00187, to which specific

reference is made and the contents of which are hereby incorporated by reference. Protection may be sought for features set out in this application in combination with features set out in that application.

The application likewise relates to the use of an accelerator in which a plurality of accelerating cells arranged to convey a beam, and adjacent cells are linked by a coupling cell, the coupling cells being arranged to dictate the ratio of electric field in the respective adjacent accelerating cells, wherein at least one coupling cell is switched between a positive ratio and a negative ratio.

Further, the application relates to an operating method for an accelerator in which a plurality of accelerating cells arranged to convey a beam, and adjacent cells are linked by a coupling cell, the coupling cells being arranged to dictate the ratio of electric field in the respective adjacent accelerating cells, wherein at least one coupling cell is switched between a positive ratio and a negative ratio.

BRIEF DESCRIPTION OF THE DRAWINGS

An embodiment of the invention will now be described by way of example, with reference to the accompanying figures, in which;

Figure 1 is a schematic illustration of a conventional linear accelerator;

Figure 2 shows a desirable electric field in the accelerator of figure 1;

Figure 3 shows a typical electric field as "observed" by an electron being accelerated;

Figure 4 shows a linear accelerator according to the present invention;

Figure 5 shows the variations of the individual coupling coefficients between cell 108 of figure 4 and the two adjacent coupling cells, and shows the variation of the ratio of these coefficients as the conductive element (the vane) is rotated;

Figures 5a and 5b proposes an explanation of figure 5;

Figure 6 shows an electric field seen by an electron for the accelerator of figure 4 with the rotatable element set to step down the E-field;

Figure 7 shows a similar electric field with the rotatable element set to step up the E-field; and

Figure 8 shows a still further electric field with the rotatable element set to reverse the E-field.

DETAILED DESCRIPTION OF THE EMBODIMENTS

Referring to figure 1, a conventional accelerator 100 has a series of accelerating cells such as 102. These are arranged in a linear array and communicate via an aperture 104 on the centreline of each. An accelerating beam of electrons passes along that path through each accelerating cell. Coupling cells such as 106 are arranged between adjacent accelerating cells and provide a degree of rf coupling

between accelerating cells. This coupling regulates an rf standing wave which is established in the accelerator by an external means (not shown).

Conventionally, the cells are numbered starting at the first accelerating cell and sequentially for each cell of whatever type. Thus the first coupling cell, between the first and second accelerating cells, is cell 2. The second accelerating cell is then cell 3. This is illustrated in figure 1, and results in accelerating cells being odd-numbered and coupling cells being even-numbered.

Figure 2 shows the desired rf pattern in the cells. It should be remembered that the pattern is that of a standing wave illustrated at an instant in time, so the actual E field at a particular location oscillates between the maximum shown in figure 2 and the reverse field. The field is ideally positive in cell 1, zero in cell 2, negative in cell 3, and zero in cell 4. It then repeats this pattern of being zero in the coupling cells and alternating polarity in successive accelerating cells. The accelerator is sized in relation to the frequency of the rf standing wave such that in the time that the accelerating electron moves from one cell to another, for example from cell 23 to cell 25, the standing wave will have completed one half cycle. As a result, the E field in cell 25 will, when the electron arrives, be the opposite of its value when the electron was in cell 23. Thus, the E field will be positive, so far as the electron observes, in every accelerating cell and the electron will steadily gain energy from the E field as it progresses.

In the later accelerating cells, the energy of the electron is such as to render its movement relativistic. As it gains energy, therefore, its speed remains substantially constant despite its rising kinetic energy. This allows the phase relationship between the rf standing wave and the progressing electron to remain fixed. It is therefore important that the beam remains relativistic, since it will otherwise fall out of synchronisation with the rf standing wave. It is not therefore possible to reduce the output energy of the beam by reducing the acceleration (ie the rf power) since although the beam would in theory be relativistic when output, it would have been non-relativistic for a substantial length of the accelerator and the beam would therefore suffer loss of phase synchronism.

Figure 3 shows a plot of the likely actual E field as observed by the electron during its passage through the accelerator. It can be seen that there are a number of points corresponding to the centres of accelerating cavities where the E field is strong and positive. Between these areas the field is small and can be ignored. Within cells, the field approximates to that desired.

Figure 4 shows a linear accelerator according to the present invention. Cell 10 is replaced with a variable coupling cell 108 which comprises a substantially cylindrical cavity 110 aligned transverse to the axis of the accelerator in which is placed a rotateable vane 112. This is as described in our earlier application PCT/GB99/00187, to which the reader is referred. As described in that application, this arrangement

allows a wide range of ratios of coupling coefficients to be obtained. However, it is now further apparent that this arrangement can in fact generate a negative ratio, as shown in figure 5. This shows the coupling coefficients and the ratio between them as the vane is rotated through 360° . It will be seen in this figure that over some ranges of vane angle, both coupling coefficients have the same sign and hence the ratio between them is positive, but that over other ranges of vane angle the coupling coefficients have different signs and hence the ratio is negative.

It is this ability of the arrangement to produce coupling coefficients that can either be of the same sign or be of opposite signs that can permit two portions of a linear accelerator either to both provide acceleration of particles or for one portion to accelerate whilst simultaneously for the other to decelerate.

In some regions, the ratio is very large indeed and the accelerator may well be unstable in these regions. However, in other areas such as between 30° and 180° on the scale as illustrated, the ratio can be varied smoothly between a moderate positive value and a moderate negative value.

Figures 5a and 5b illustrate how this is believed to arise. Within the cavity, the orientation of the entire EM field pattern is dictated by the position of the vane 112, since (for instance) the E-field (114) lines must meet a conductive surface perpendicularly. However, RF coupling between the accelerating cells and coupling cell

is predominantly magnetic with the axial H-field indicated by arrow ends (x and -) according to whether the field points into or out of the page).

Thus when the vane 112 is between ports 116, 118 (figure 5a) linking the accelerating and coupling cells, each port will see an H-field of the same polarity (e.g. both x), giving rise to a positive coupling coefficient ratio and electron acceleration both upstream and downstream of the coupling cell. In general, these accelerating field strengths will differ according to the exact angular setting of the vane.

When the vane 112 is transverse to the ports 116, 118 (figure 5b), the polarity of the H-fields seen by the ports will be opposite (eg x and -) giving rise to a negative coupling coefficient ratio and thus electron acceleration upstream and deceleration downstream of the coupling cell.

Figures 6 and 7 show the effect on the accelerating cell E fields of a coupling coefficient ratio greater than unity and less than unity respectively. In figure 6, after cell 10, the electric field experienced by the accelerating beam drops, and the beam will therefore gain less energy and the output energy will be less. In figure 7, after cell 10, the electric field experienced by the accelerating beam rises, and the beam will therefore gain more energy and the output energy will be greater. This illustrates the ability of the apparatus of PCT/GB99/00187 to vary the output energy of the beam.

Figure 8 shows the effect of a negative coupling coefficient ratio. The E field from cell 9 to cell 11 is reversed, effectively a phase change in the rf standing wave. Thus, from cell 11 onwards, the beam experiences an E field which acts to decelerate it, ie it loses energy to the E field. Thus, the beam output can be of a very low energy indeed. This enables a portal image to be taken with adequate contrast.

Attempts have previously been made to insert a phase change in the rf field by separating it from the beam and inserting an additional half wavelength path, but this raises severe difficulties in reuniting the rf and the beam. This arrangement avoids this difficulty entirely.

It will of course be apparent to those skilled in the art that many variations could be made to the above arrangements without departing from the scope of the present invention.

CLAIMS

[Amended - PCT Chapter II]

1. An accelerator comprising a plurality of accelerating cells arranged to convey a beam, adjacent cells being linked by a coupling cell, the coupling cells being arranged to dictate the ratio of electric field in the respective adjacent accelerating cells, at least one coupling cell being variable to allow a range of ratios including positive values and negative values.
2. An accelerator according to claim 1 in which the at least one coupling cell is variable smoothly from a positive value to a negative value.
3. An accelerator according to claim 1 or claim 2 in which the beam is relativistic over substantially the length of the accelerator.
4. An accelerator according to any one of the preceding claims in which the variable coupling cell comprises a cavity containing a conductive element rotatable about an axis transverse to the beam axis.
5. The use of an accelerator in which a plurality of accelerating cells are arranged to convey a beam, and adjacent cells are linked by a coupling cell, the coupling cells being arranged to dictate the ratio of electric field in the respective

00949794-GB0003004

adjacent accelerating cells, at least one coupling cell being variable to allow a range of ratios including positive values and negative values.

6. Use according to claim 5 in which the at least one coupling cell is variable smoothly from a positive value to a negative value.
7. An operating method for an accelerator in which a plurality of accelerating cells are arranged to convey a beam, and adjacent cells are linked by a coupling cell, the coupling cells being arranged to dictate the ratio of electric field in the respective adjacent accelerating cells, at least one coupling cell being variable to allow a range of ratios including positive values and negative values.
8. The method of claim 7 in which the at least one coupling cell is variable smoothly from a positive value to a negative value.
9. The use of an accelerator according to any one of claims 1 to 4 for taking kilovoltage portal images.
10. An accelerator substantially as described herein with reference to and/or as illustrated in the accompanying figures 4 to 8.




Fig 1




Fig 2




Fig 4




Fig 3




Fig 5

3/4




Fig 5a




Fig 5b




Fig 6

4/4




Fig 7




Fig 8

DECLARATION FOR UTILITY PATENT APPLICATION (37 C.F.R. 1.63)	Attorney Docket No.	
	First Named Inventor	ALLEN, John
	Filed	

As a below named inventor, I hereby declare that my residence, post office address, and citizenship are as stated below.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled: LINEAR ACCELERATOR the specification of which:

— is attached hereto; and/or

X was filed on 3 August 2000 as PCT International Application Number PCT/GB00/03004

and was amended under PCT Article 19 on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 C.F.R. 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application Number(s)	Country	Foreign Filing Date (MM/DD/YYYY)	Certified Copy Attached?		No Priority Claimed?
			Yes	No	
9918787.4	GB	August 10, 1999	No		

I hereby claim the benefit under 35 U.S.C. 119(e) of any United States provisional application(s) listed below.

Application Number(s)	Filing Date (MM/DD/YYYY)

I hereby claim the benefit under 35 U.S.C. 120 of any United States application(s), or 365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT international application in the manner provided by the first paragraph of 35 U.S.C. 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 C.F.R. 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.


U.S. Parent Application or PCT Parent Number	Parent Filing Date (MM/DD/YYYY)	Parent Patent Number (if applicable)
PCT/GB00/03004	August 3, 2000	

DIRECT ALL CORRESPONDENCE TO:

Name	
Address	Kinney & Lange, P.A. The Kinney & Lange Building 312 South Third Street Minneapolis, Minnesota 55415-1002 United States
Telephone	(612) 339-1863
Fax	(612) 339-6580

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

180

Sole or First Inventor:	
Given Name (First and middle (if any))	
John	Family Name or Surname
	ALLEN
Inventor's signature	
	Date: 3 JAN 2002
Residence City, Country	Haywards Heath, GB GBX
Post Office Address	65 Edward Road,
City, State, Country	Haywards Heath, West Sussex RH16 4QL, GB

Second Inventor:	
Given Name (First and middle (if any)) Family Name or Surname	
<u>Leonard Knowles</u> <u>BRUNELLE</u>	
Inventor's signature	<u>L K Brunelle</u>
Date: <u>21 Dec. 2001</u>	
Residence City, Country	<u>Haywards Heath, GB</u> <u>GBX</u>
Citizenship: GB	
Post Office Address	63 Pasture Hill Road
City, State, Country	Haywards Heath, West Sussex RH16 1LY, GB

Third Inventor:	
Given Name (First and middle (if any)) Family Name or Surname	
<u>Terry Arthur</u> <u>LARGE</u>	
Inventor's signature	<u>Terry Arthur</u>
Date: <u>21 December 2001</u>	
Residence City, Country	<u>Lindfield, GB</u> <u>GBX</u>
Citizenship: GB	
Post Office Address	"Arley", 5 Beckworth Lane
City, State, Country	Lindfield, West Sussex RH16 2EH, GB

Fourth Inventor:	
Given Name (First and middle (if any)) Family Name or Surname	
<u>Terence</u> <u>BATES</u>	
Inventor's signature	<u>Terence Bates</u>
Date: <u>22 December 2001</u>	
Residence City, Country	<u>Horsham, GB</u> <u>GBX</u>
Citizenship: GB	
Post Office Address	75 Smithbarn
City, State, Country	Horsham, West Sussex RH13 6DT, GB

United States Patent & Trademark Office
Office of Initial Patent Examination -- Scanning Division



SCANNED, #24.

Application deficiencies found during scanning:

Page(s) 11 of Specifications (Document title) were not present for scanning.

Page(s) _____ of _____ (Document title) were not present for scanning.

Scanned copy is best available.